



# DAX for Power BI

Sample manual - first two chapters



**Wise Owl**  
Training

## TABLE OF CONTENTS (1 of 5)

1	INTRODUCTION TO DAX IN POWER BI	Page
1.1	DAX in Power BI	7
	<i>How DAX is Used 1 – Calculated Columns</i>	7
	<i>How DAX is Used 2 – Measures</i>	7
	<i>How DAX is Used 3 – Calculated Tables</i>	8
	<i>Choosing the Type of Calculation</i>	8
	<i>Where Else is DAX Used?</i>	8
1.2	The Construct-a-Creature Database	9
	<i>The Tables and Relationships</i>	9
1.3	Getting Help with DAX	10
	<i>Getting Help within Power BI</i>	10
	<i>Other Sources of Help</i>	10

2	BASIC CALCULATED COLUMNS	Page
2.1	Calculated Columns	11
	<i>Key Features of Calculated Columns</i>	11
	<i>Creating a Calculated Column</i>	11
	<i>Entering a Formula</i>	12
	<i>Calculated Column Properties</i>	13
	<i>Using Calculated Columns in Visuals</i>	13
2.2	Referencing Columns and Tables	14
	<i>Qualifying Column Names</i>	14
	<i>Table Names</i>	14
	<i>Referencing Columns in Other Tables</i>	15
	<i>The Related Function</i>	15
2.3	Editing DAX Code	16
	<i>Multiple Lines and Indenting</i>	16
	<i>Comments</i>	17
	<i>Keyboard Shortcuts</i>	17

3	WORKING WITH DATA TYPES	Page
3.1	DAX Data Types	18
	<i>Viewing a Column's Data Type</i>	18
3.2	Working with Numbers	19
	<i>Basic Arithmetic</i>	19
	<i>Controlling the Calculation Order</i>	19
	<i>Safely Dividing Numbers</i>	20
	<i>Numeric Functions</i>	21
3.3	Working with Text	22
	<i>Writing Text in Calculations</i>	22
	<i>Concatenating Text</i>	22
3.4	Text Functions	23
	<i>Finding and Extracting Text</i>	23
	<i>Replacing Text</i>	23
	<i>Generating Text</i>	24
	<i>Converting and Formatting Text</i>	24
3.5	Working with Dates	25
	<i>Entering Date and Time Values</i>	25
	<i>Returning the Current Date and Time</i>	25
	<i>Calculating Date and Time Values</i>	26
	<i>Calculating the Difference Between Dates</i>	26
	<i>Extracting Date Parts</i>	27
	<i>Formatting Dates</i>	27

4	CONDITIONAL FUNCTIONS	Page
4.1	The IF Function	28
	<i>Testing a Single Condition</i>	28
	<i>Comparison Operators</i>	28
	<i>The IN Operator</i>	28
	<i>Nesting IF Functions</i>	29
	<i>Combining Logical Tests</i>	29
	<i>The NOT Operator</i>	29
4.2	Working with Blanks	30
	<i>Producing a Blank</i>	30
	<i>Blank Arithmetic</i>	30
	<i>Testing for Blanks</i>	30
	<i>The COALESCE Function</i>	31
4.3	Testing for Errors	32
	<i>The ISERROR and IFERROR Functions</i>	32
	<i>Avoiding Error Functions</i>	32
4.4	The SWITCH Function	33
	<i>A Simple SWITCH Function</i>	33
	<i>Logical Tests in a SWITCH Function</i>	33

## TABLE OF CONTENTS (2 of 5)

5	BASIC MEASURES	Page
5.1	Introduction to Measures	34
	<i>Measures vs. Calculated Columns</i>	34
	<i>Implicit Measures</i>	34
5.2	Creating a Measure	35
	<i>Adding a Measure to a Table</i>	35
	<i>Formatting Measures</i>	36
	<i>Displaying a Measure in a Visual</i>	36
	<i>Referencing Measures</i>	37
5.3	Filter Context	38
	<i>What is Filter Context?</i>	38
	<i>How DAX Applies Filter Context</i>	39
5.4	Measures Tables	40
	<i>Creating a Separate Measures Table</i>	40
	<i>Moving Measures</i>	41
5.5	Quick Measures	42
	<i>Creating a Quick Measure</i>	42
	<i>Editing a Quick Measure</i>	43
	<i>Using a Quick Measure</i>	43

6	AGGREGATION FUNCTIONS	Page
6.1	Aggregating Column Values	44
	<i>Basic Aggregation Functions</i>	44
	<i>Functions for Counting</i>	45
	<i>Dealing with Boolean Values</i>	45
6.2	Aggregating Expressions	46
	<i>The AggregateX Functions</i>	46
6.3	Iterators and Row Context	47
	<i>A Reminder of Filter Context</i>	47
	<i>Row Context in Iterator Functions</i>	48
	<i>The Final Result</i>	48
	<i>How to Spot Iterators</i>	48

7	THE CALCULATE FUNCTION	Page
7.1	Introducing the CALCULATE Function	49
	<i>Expressions in the CALCULATE Function</i>	49
7.2	Adding New Filters	50
	<i>Basic Filter Expressions</i>	50
	<i>Adding Multiple Filters</i>	51
	<i>Filter Arguments and Filter Context</i>	51
	<i>Multiple Columns in Filter Arguments</i>	52
7.3	Replacing Filters	53
	<i>Replacing an Existing Filter</i>	53
	<i>Comparing Differently Filtered Measures</i>	54
	<i>Dealing with Blank Values</i>	54
7.4	Keeping Filters	55
	<i>The Problem with the Default Behaviour</i>	55
	<i>The KEEPFILTERS Function</i>	56
	<i>Using the VALUES Function</i>	56
7.5	Removing Filters	57
	<i>Removing Every Filter</i>	57
	<i>Using the ALL Function</i>	58
	<i>Comparing Filtered and Unfiltered Values</i>	58
	<i>Removing Filters from Specific Fields</i>	59
	<i>An Issue with Sort-By Fields</i>	60
	<i>Removing Filters from a Specific Table</i>	60
7.6	Special Filter Removal Functions	61
	<i>The ALLEXCEPT Function</i>	61
	<i>The ALLSELECTED Function</i>	62

8	VARIABLES	Page
8.1	Introduction to Variables	63
	<i>Using Variables in Measures</i>	63
8.2	How Variables are Evaluated	64
	<i>Lazy Evaluation</i>	64
	<i>DAX Variables are Constants</i>	64
8.3	Debugging with Variables	65
	<i>Returning Different Variables</i>	65
8.4	Nesting Variables	66
	<i>Variables in Functions</i>	66
	<i>Variable Scope</i>	67

## TABLE OF CONTENTS (3 of 5)

9	THE FILTER FUNCTION	Page
9.1	Introduction to the FILTER Function	68
	<i>A Basic FILTER Example</i>	68
	<i>Using the CALCULATE Function</i>	68
	<i>How CALCULATE and FILTER are Related</i>	69
	<i>Using Multiple Filters</i>	69
	<i>Using Variables</i>	69
9.2	FILTER vs. CALCULATE	70
	<i>Referencing Multiple Fields</i>	70
	<i>Using Fields from Different Tables</i>	70
	<i>Referring to Measures</i>	71
	<i>Replacing Filters</i>	72
9.3	The CALCULATETABLE Function	73
	<i>Using CALCULATETABLE</i>	73

10	FILTERS AND RELATIONSHIPS	Page
10.1	Relationships and Filter Direction	74
	<i>The Problem with Relationships</i>	74
	<i>Changing the Cross Filter Direction</i>	75
	<i>Solving the Problem using Filters</i>	76
10.2	Cross Filter Direction in Measures	77
	<i>The CROSSFILTER Function</i>	77
	<i>Using Single and Both Filter Directions Simultaneously</i>	78
	<i>Multiple CROSSFILTER Functions</i>	78

11	CONTEXT TRANSITION	Page
11.1	What is Context Transition?	79
	<i>Row and Filter Context</i>	79
11.2	Context Transition in Calculated Columns	80
	<i>Row Context in Calculated Columns</i>	80
	<i>Performing Context Transition</i>	80
	<i>Implicit Context Transition</i>	81
	<i>The RELATEDTABLE Function</i>	81
11.3	Context Transition in Measures	82
	<i>Row Context in Measures</i>	82
	<i>Context Transition in Measures</i>	83
	<i>The Effect of Filter Context</i>	83
	<i>Removing Filters</i>	84
11.4	Ranking Values	85
	<i>The RANKX Function</i>	85
	<i>Ranking in Calculated Columns</i>	85
	<i>Context Transition in Calculated Columns</i>	86
	<i>Ranking in Measures</i>	86

12	TIME INTELLIGENCE	Page
12.1	Introduction to Time Intelligence	87
	<i>Calendar Tables</i>	87
	<i>The Date Column</i>	88
	<i>Referring to Calendar Tables</i>	88
12.2	Time Intelligence Functions	89
	<i>General Time Intelligence Functions</i>	89
	<i>Using the DATEADD Function</i>	89
	<i>How DATEADD Works</i>	90
	<i>Using the DATESINPERIOD Function</i>	90
	<i>Using the Current Date</i>	91
	<i>Using Specific Dates</i>	91
12.3	To Date Calculations	92
	<i>Returning Date Ranges</i>	92
	<i>Calculating Running Totals</i>	92
	<i>Total To Date Functions</i>	93
	<i>Easier Running Total Calculations</i>	93
	<i>Specifying Year End Dates</i>	94
	<i>Calculating Life to Date Values</i>	94
12.4	Next and Previous Periods	95
	<i>Next and Previous Period Functions</i>	95
	<i>Comparing Entire Previous Years</i>	96
	<i>Comparing Parts of Previous Years</i>	97
12.5	Period Start and End Dates	98
	<i>Period Start and End Functions</i>	98
	<i>Start and End Dates</i>	99
	<i>Opening and Closing Balances</i>	100
	<i>First and Last Non-Blank Dates</i>	100
	<i>First and Last Non-Blank Values</i>	101
	<i>Non-Blank Opening Balances</i>	101
12.6	Moving Averages	102
	<i>Calculating a Moving Average</i>	102

## TABLE OF CONTENTS (4 of 5)

13	CUSTOM CALENDARS	Page	14	DYNAMIC MEASURES	Page
13.1	Why use Custom Calendars?	103	14.1	Dynamic Labels	115
	<i>Disabling Automatic Calendars</i>	103		<i>Why use Dynamic Labels?</i>	115
13.2	Creating a Custom Calendar	104	14.2	Returning a Single Value	116
	<i>The CALENDARAUTO and CALENDAR Functions</i>	104		<i>The VALUES Function</i>	116
	<i>Adding Extra Columns</i>	105		<i>Testing for a Single Value</i>	117
	<i>Financial Years</i>	106		<i>The SELECTEDVALUE Function</i>	117
13.3	Finishing the Calendar	107	14.3	Concatenating Values	118
	<i>Marking as a Date Table</i>	107		<i>The CONCATENATEX Function</i>	118
	<i>Changing Default Aggregations</i>	107		<i>More Complex Expressions</i>	118
	<i>Setting Sort-By Columns</i>	108	14.4	Filtered Values	119
	<i>Creating Hierarchies</i>	108		<i>Testing for Filtered Values</i>	119
	<i>Hiding Fields</i>	109		<i>Testing for Cross Filtered Values</i>	119
	<i>Creating a Relationship</i>	109		<i>Selecting the Top N Rows</i>	120
13.4	Using a Custom Calendar	110	14.5	Disconnected Slicers	121
	<i>Creating Visuals</i>	110		<i>Creating a Disconnected Table</i>	121
	<i>Time Intelligence Functions</i>	110		<i>Creating a Disconnected Slicer</i>	122
13.5	Multiple Date Fields	111		<i>Referencing the Selected Value</i>	122
	<i>Using Multiple Calendars</i>	111	14.6	Formatting with Measures	123
	<i>Using a Single Calendar</i>	112		<i>Calculating Colours with Measures</i>	123
	<i>Changing the Active Relationship</i>	112		<i>Using Measures in Conditional Formatting</i>	124
	<i>The USERELATIONSHIP Function</i>	113		<i>Choosing Colours with Slicers</i>	124
13.6	Special Dates	114			

## TABLE OF CONTENTS (5 of 5)

15	VISUAL CALCULATIONS	Page
15.1	What are Visual Calculations?	125
15.2	Creating Visual Calculations	126
	<i>Creating a Visual</i>	126
	<i>Adding a Visual Calculation</i>	126
	<i>Writing the Formula</i>	127
	<i>Using Pre-Defined Visual Calculations</i>	128
15.3	Editing a Visual Calculation	129
	<i>Formatting the Results</i>	129
	<i>Editing the Formula</i>	129
15.4	Hiding Fields in a Visual	130
15.5	Running Totals	131
	<i>Calculating a Running Total</i>	131
	<i>Running Totals and Hierarchies</i>	131
	<i>Resetting a Running Total</i>	132
	<i>Changing the Direction</i>	133
15.6	Moving Averages	134
	<i>Calculating a Moving Average</i>	134
	<i>Excluding the Current Row</i>	134
15.7	Referring to Other Rows	135
	<i>Next and Previous Rows</i>	135
	<i>Setting the Step Value</i>	136
	<i>First and Last Rows</i>	136
15.8	Referring to Parent Values	137
	<i>Collapsing Filters</i>	137
	<i>Collapsing Filters Relatively</i>	138
	<i>Collapsing All Filters</i>	138
15.9	Referring to Child Rows	139
	<i>Expanding Filters</i>	139
	<i>Expanding Filters Relatively</i>	139
15.10	Controlling Group Headers	140
	<i>Testing for the Presence of a Column</i>	140

## CHAPTER 1 - INTRODUCTION TO DAX IN POWER BI

### 1.1 DAX in Power BI

In Power BI you can use the *DAX (Data Analysis eXpressions)* language to create *calculated columns*, *measures* and *tables*. You can see an example of each below.

#### How DAX is Used 1 – Calculated Columns

A *calculated column* is like a formula in an Excel table. The results of a calculated column are stored in the data model.

1 Sale value = Sales[Price] * Sales[Quantity]					
SaleDate	ProductId	Centrelid	Quantity	Price	Sale value
21 July 2023	10	101	1	£3.99	£3.99
21 July 2023	12	178	2	£6.99	£13.98
21 July 2023	13	207	1	£3.95	£3.95
21 July 2023	13	342	4	£3.95	£15.80

This calculated column gives the value for each row of a sales table by multiplying the price of an item by the quantity sold.

As we will see in this manual, a calculated column is evaluated for each row of a table; DAX uses the *row context* to access the correct values for each separate calculation.

#### How DAX is Used 2 – Measures

A *measure* is a formula which calculates a value when you place it in a visual. The visual provides a *filter context* which tells the measure which values it can use in the calculation.

<pre> 1 Sum of sale value = SUMX( 2   Sales, 3   Sales[Price] * Sales[Quantity] 4 ) </pre>				
RegionName	Air	Land	Water	Total
East Anglia	1,268.71	13,640.28	2,050.91	16,959.90
East Midlands	2,609.87	26,289.48	5,033.67	33,933.02
London	4,899.45	54,018.62	9,136.50	68,054.57
North	2,874.62	25,980.55	4,334.49	33,189.66
North West	7,950.17	69,751.18	12,614.71	90,316.06
South East	10,697.97	102,171.04	17,507.12	130,376.13
South West	2,616.48	23,769.80	4,506.69	30,892.97
West Midlands	4,702.33	49,116.82	8,878.73	62,697.88
Yorkshire & Humberside	6,231.78	47,396.27	8,509.78	62,137.83
<b>Total</b>	<b>43,851.38</b>	<b>412,134.04</b>	<b>72,572.60</b>	<b>528,558.02</b>

This measure multiplies the price of an item by the quantity sold for each row of a sales table, then sums the results.

When we place the measure in a visual (a matrix in this case) the measure is calculated for each data point in the visual.

The filter context controls which values the measure can access. This cell gives the total sales value for products in the **Water** environment sold in the **South West** region.

## How DAX is Used 3 – Calculated Tables

Although most of the tables in your Power BI data model will be created by importing data, you can also use DAX to calculate tables. It's common to use this technique to create custom calendars.

The screenshot shows the DAX editor with the following code:

```
1 Sales Calendar = ADDCOLUMNS(
2     CALENDAR(
3         DATE(YEAR(MIN(Sales[SalesDate])), 1, 1),
4         DATE(YEAR(MAX(Sales[SalesDate])), 12, 31)
5     ),
6     "Year", YEAR([Date]),
7     "Month", MONTH([Date]),
8     "Month Name", FORMAT([Date], "MMMM"),
9     "Day", DAY([Date])
10 )
```

A callout box points to the `CALENDAR` function, stating: "This DAX expression creates a calculated table which contains a range of dates related to the sales in our database."

Below the code, a preview table is shown:

Date	Year	Month	Month Name	Day
01/01/2020 00:00:00	2020	1	January	1
02/01/2020 00:00:00	2020	1	January	2
03/01/2020 00:00:00	2020	1	January	3

## Choosing the Type of Calculation

Power BI provides several ways to create calculated columns, measures and tables. One way is to click the relevant tool on the **Home** tab of the ribbon while in the **Data** view.

The screenshot shows the Power BI ribbon with the **Home** tab selected. The **Calculations** group is highlighted, containing four buttons: **New measure**, **Quick measure**, **New column**, and **New table**.

Callout boxes provide instructions:

- "Select the **Data view** tool on the left of the Power BI window." (points to the Data view icon in the left-hand pane)
- "The **Calculations** group on the **Home** tab of the ribbon has a button for each type of DAX calculation." (points to the Calculations group on the ribbon)

## Where Else is DAX Used?

In addition to Power BI, you can write DAX in the following applications:

Application	Description
Power Pivot	Power Pivot is an add-in for Excel which allows you to combine data from multiple sources and present this in a pivot table or chart.
SQL Server Analysis Services (SSAS) Tabular	SSAS Tabular Model allows you to combine data from lots of different data sources, apply security to it to control who sees what and then allow employees of your organisation to share the resulting data model.




## 1.2 The Construct-a-Creature Database

This courseware uses data from the (fictitious) Wise Owl subsidiary **Construct-a-Creature** (a retail chain loosely modelled on Build-a-Bear, but with a wider range of animals available for purchase).

## The Tables and Relationships

You can see the tables and relationships of the database in the diagram below:

There are four tables representing a geographical dimension to do with where sales took place. These tables give the shopping centre, type of centre, town and region.



There are also four tables representing a product dimension. These give details of the product sold (for example, a frog is an amphibian which lives in a fresh water habitat in a watery environment).


The **Sales** table stores how many of each product were sold in each transaction.

## 1.3 Getting Help with DAX

The amount of help available for DAX both within Power BI and from third parties has increased dramatically since the product was first released.

### Getting Help within Power BI

You'll see various popups appear to help you as you write DAX in Power BI.



### Other Sources of Help

You can find more descriptive help for DAX on a range of websites, as shown in the table below:

Website	Description	URL
<i>Microsoft DAX Reference</i>	Microsoft's official documentation for DAX functions. It's somewhat dry but a useful technical reference.	<a href="https://learn.microsoft.com/en-us/dax/">https://learn.microsoft.com/en-us/dax/</a>
<i>Power BI Community</i>	A Microsoft forum in which you can post questions about any aspect of Power BI and rely on other members to provide answers.	<a href="https://community.fabric.microsoft.com/t5/Microsoft-Power-BI-Community/ct-p/powerbi">https://community.fabric.microsoft.com/t5/Microsoft-Power-BI-Community/ct-p/powerbi</a>
<i>SQLBI</i>	A third-party site maintained by Marco Russo and Alberto Ferrari. The site contains lots of free resources to help you with DAX.	<a href="https://www.sqlbi.com/">https://www.sqlbi.com/</a>
<i>DAX Guide</i>	A third-party alternative to Microsoft's DAX Reference created by the Italians. This site fleshes out the detail of DAX functions and provides links to helpful articles which describe in more detail how the functions work.	<a href="https://dax.guide/">https://dax.guide/</a>
<i>Wise Owl</i>	The Wise Owl website contains lots of free resources including videos, blogs and exercises to help you with learning DAX.	<a href="https://www.wiseowl.co.uk/resources/">https://www.wiseowl.co.uk/resources/</a>

## CHAPTER 2 - BASIC CALCULATED COLUMNS

### 2.1 Calculated Columns

A *calculated column* is a type of calculation you can create using DAX in Power BI. This chapter shows you the basics of writing DAX using calculated columns.

#### Key Features of Calculated Columns

You can see some of the key features of calculated columns in the table below:

Feature	Description
<i>Created in data tables</i>	You create a calculated column in a table in the data model. The calculated column can refer directly to any column in the same table.
<i>Calculated immediately</i>	A calculated column produces its results as soon as you enter it. The values are updated whenever the data model is refreshed.
<i>Stores data in the model</i>	A calculated column stores its results in the data model. Each calculated column you create increases the storage space required by the model.
<i>Uses row context</i>	The expression in a calculated column is evaluated for each row in the table. The row context provides the expression with access to values on the same row in the table.

#### Creating a Calculated Column

You can create a calculated column in any of the three Power BI views but, if you want to see the results of your calculation, it's best to select the **Data** view.

Select the **Data view** button on the left of the Power BI window.

You can right-click on any column in the table and choose **New column** to add a calculated column.


You can choose **New column** from the **Table tools** or **Home** tabs of the ribbon to add a calculated column.

You can right-click the table in the **Data** panel and choose **New column** to add a calculated column.


## Entering a Formula

After choosing to create a calculated column you can enter your DAX code in the formula bar below the ribbon. The example below multiplies one column by another to create a new value:


- 1) Start by giving the column a sensible name.




- 2) To reference a column in the same table, simply begin typing the column name.




- 3) Type in an operator then reference the next column.



- 4) Press **Enter** to commit the formula.



Your calculated column will appear in the table in the **Data** pane with a special symbol to indicate its status.



## Calculated Column Properties

Once you've created a calculated column, you can modify it in the same way as any other column in your data model, as shown in the diagram below.

The diagram illustrates the process of modifying a calculated column's properties. It shows the **Data** pane where the **Sale Value** column is selected. The **Column tools** ribbon is then shown, with the **Column properties** pane open. The pane is divided into three sections: **Structure**, **Formatting**, and **Properties**. The **Structure** section includes the **Name** (Sale Value) and **Data type** (Decimal number). The **Formatting** section includes the **Format** (General) and **Number format** (Auto). The **Properties** section includes the **Summarization** (Sum) and **Data category** (Uncategorized).

Select the column in the **Data** pane. You can then use the **Column tools** tab in the ribbon to modify its properties.


You can change the default aggregation function used when you add the column to a visual using this drop-down list.

You can apply formatting to the column using these tools.

You can assign a data category to the column using this drop-down list.

## Using Calculated Columns in Visuals

You can use a calculated column to populate visuals in your report, just as for any other column in your data model.



## 2.2 Referencing Columns and Tables

This section shows you various ways to refer to columns and tables in your DAX formulae.

### Qualifying Column Names

When you select a column name from the Intellisense list, it will be automatically qualified with the name of the table to which it belongs. You don't have to include the table name, however.

```
1 Average Unit Size = Centre[SquareMetres] / Centre[NumberUnits]
```

```
1 Average Unit Size = [SquareMetres] / [NumberUnits]
```

These two formulae give the same result.

Although you don't always have to include the table name when referencing a column, it makes sense to do so for the following reasons:

- If you always include the table name you don't have to remember when it is or isn't required.
- It allows you to spot when you're referring to a column as opposed to, say, a measure.
- When a column name exists in multiple tables it makes the reference unambiguous.

### Table Names

If the name of a table contains spaces, or it conflicts with another DAX keyword, you must enclose the table name in single quotes.

```
1 Sale value = 'Sales Table'[Price] * 'Sales Table'[Quantity]
```


**Sales Table** must be enclosed in single quotes due to the space in the table name.



*You can always enclose a table name in single quotes, even when it isn't required.*

## Referencing Columns in Other Tables

In a calculated column you can only directly reference other columns which belong to the same table. This is a problem when your calculation needs to refer to columns in other tables!



We'd like to create a calculated column in the **Sales** table which multiplies the **Quantity** by the **ProductionCost** in the **Product** table.

```
1 Sale cost = Sales[Quantity] * Product[ProductionCost]
```

! A single value for column 'ProductionCost' in table 'Product' cannot be

When we reference the **ProductionCost** column directly, the formula results in an error.


## The Related Function

The key to solving the above problem is that the **Product** and **Sales** tables have a relationship. This allows us to use the **RELATED** function to reference a column in a related table.

```
1 Sale cost = Sales[Quantity] * RELATED(Product[ProductionCost])
```

We can successfully reference the **ProductionCost** column by using the **RELATED** function.

You can reference columns from a table at the **1** end of a relationship, regardless of how many steps it takes. In our model, the **Sales** table sits at the many end of every relationship:



A calculated column in the **Sales** table can reference any other column in the data model using the **RELATED** function.

In the **Sales** table you could return the **RegionName** with this formula:

```
=RELATED(
  Region[RegionName]
)
```

## 2.3 Editing DAX Code

Although you can write a DAX formula as a continuous stream of code, there are several things you can do to make your code more readable.

```
1 Sale Value % of Total = IF(NOT(ISBLANK(SUMX(Sales,Sales[Price]*Sales
[Quantity]))),DIVIDE(SUMX(Sales,Sales[Price]*Sales[Quantity]),
CALCULATE(SUMX(Sales,Sales[Price]*Sales[Quantity]),REMOVEFILTERS()))))
```

Laying out a formula like this makes it very difficult to work with!



*It's not important to understand what the code in this section does – instead, focus on the techniques used to make it more readable.*

### Multiple Lines and Indenting

You can break a formula onto multiple lines and add tab spaces to make it more readable. You can use the following keys to add new lines and indenting to a formula:

Key	What it does
Shift + Enter or Alt + Enter	Adds a new line, and a tab level if appropriate.
Tab	Indents the highlighted lines one tab space.
Shift + Tab	Outdents the highlighted lines one tab space.

You can see an example of a formula with new lines and indenting in the diagram below:

When you use a function (in this case **DIVIDE**), open the round brackets then start a new line and add a tab space.

Close the brackets for a function at the same indent level as the line on which the brackets were opened. Use the vertical grey lines to help you put the brackets in the right place.

```
1 Sale Value % of Total = DIVIDE(
2     SUMX(
3         Sales,
4         Sales[Price]*Sales[Quantity]
5     ),
6     CALCULATE(
7         SUMX(
8             Sales,
9             Sales[Price]*Sales[Quantity]
10        ),
11        REMOVEFILTERS()
12    )
13 )
```

Each new function that you use should have its arguments indented one extra tab level.

All of the arguments for a single function should be at the same tab level.

Use a comma at the end of a line to separate one argument from the next.



## Comments

You can use *comments* to annotate your code. You can add a comment at the end of any line after the = sign in a formula.

```

1 Sale Value % of Total = //divide filtered sales by all sales
2 DIVIDE(
3     SUMX( --calculate filtered sales
4         Sales,
5         Sales[Price]*Sales[Quantity]
6     ),
7     /*
8         remove filters
9         to get unfiltered sales
10    */
11    CALCULATE(

```

You can type // to begin adding a comment, followed by the comment text.

You can also begin a comment using -- rather than //.

Start a multi-line comment with /\* and end it with \*/ as shown here.

## Keyboard Shortcuts

You can use a range of keyboard shortcuts to help you edit your DAX code. You can see some of these in the table below:

Key	What it does
Ctrl + G	Goto the specified line number.
Alt + ↑ / Alt + ↓	Move the line of code up / down.
Shift + Alt + ↑ / Shift + Alt + ↓	Copy the line of code up / down.
Ctrl + Shift + \	Jump to the paired bracket.
Alt + Left mouse click	Add a text cursor at the clicked position.
Ctrl + L	Select the line of code.
Ctrl + Shift + L	Select all occurrences of the current selection.
Ctrl + F2	Select all occurrences of the current word.
Ctrl + /	Comment/uncomment the line of code.
Ctrl + = / Ctrl + -	Zoom in / zoom out.
Ctrl + Space Bar	Show the Intellisense list.
Ctrl + I	Show and hide tooltips.
Ctrl + J	Expand and collapse the formula bar.

Blank lined area for writing.



Blank lined area for writing.



Blank lined area for writing.



Blank lined paper for writing.



Blank lined paper for writing.



Blank lined paper for writing.



**WiseOwl**  
Training

Blank lined paper for writing.



**WiseOwl**  
Training





Blank lined paper for writing.






































**WiseOwl**  
Training

Blank lined paper for writing.



## What we do!

		Basic training	Advanced training	Systems / consultancy
Office	Microsoft Excel			
	VBA macros			
	Office Scripts			
	Microsoft Access			
Power BI, etc	Power BI and DAX			
	Power Apps			
	Power Automate (both)			
SQL Server	SQL			
	Reporting Services			
	Report Builder			
	Integration Services			
	Analysis Services			
Coding	Visual C#			
	VB programming			
	MySQL			
	Python			



**WiseOwl**  
Training

